

Features:

- Isolated mounting base 2500V~
- Pressure contact technology with Increased power cycling capability
- Space and weight saving

Typical Applications

- AC/DC Motor drives
- Various rectifiers
- DC supply for PWM inverter

V_{RSM}	V_{RRM}	品名
900V	800V	Mx1000D80W
1100V	1000V	Mx1000D100W
1300V	1200V	Mx1000D120W
1500V	1400V	Mx1000D140W
1700V	1600V	Mx1000D160W
1900V	1800V	Mx1000D180W

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T_j (°C)	VALUE			UNIT
				Min.	Typ.	Max.	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Single side cooled, $T_c=60^\circ\text{C}$	150			1000	A
$I_{F(RMS)}$	RMS forward current		150			1570	A
I_{RRM}	Repetitive peak current	at V_{RRM}	150			40	mA
I_{FSM}	Surge forward current	10ms half sine wave $V_R=0.6V_{RRM}$	150			24	kA
I^2t	I^2t for fusing coordination					2880	$\text{A}^2\text{s} \times 10^3$
V_{FO}	Threshold voltage		150			0.75	V
r_F	Forward slope resistance					0.25	$\text{m}\Omega$
V_{FM}	Peak forward voltage	$I_{FM}=3000\text{A}$	25			1.82	V
$R_{th(j-c)}$	Thermal resistance Junction to case	D.C. Single side cooled per chip				0.065	$^\circ\text{C}/\text{W}$
$R_{th(c-h)}$	Thermal resistance case to heatsink	D.C. Single side cooled per chip				0.018	$^\circ\text{C}/\text{W}$
V_{iso}	Isolation voltage	50Hz,R.M.S., $t=1\text{min}$, $I_{iso}:1\text{mA(max)}$		2500			V
F_m	Terminal connection torque(M12)					14.0	$\text{N}\cdot\text{m}$
	Mounting torque(M8)					12.0	$\text{N}\cdot\text{m}$
T_{stg}	Stored temperature			-40		125	$^\circ\text{C}$
W_t	Weight					3460	g
Outline	M15						

Nips Diode Modules (Water Cooling) MD1000D**W MC1000D**W MR1000D**W




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6






Fig.7



Unmarked dimensional tolerance : $\pm 0.5\text{mm}$