

Nips Diode Modules (Water Cooling) MD1200D**W MC1200D**W MR1200D**W

Features :

- Isolated mounting base 3000V~
- Pressure contact technology with
Increased power cycling capability
- Space and weight saving

Typical Applications :

- Various rectifiers
- DC supply for PWM inverter

V _{RRM}	品名
2000V	Mx1200D200W
2200V	Mx1200D220W
2500V	Mx1200D250W

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min.	Typ.	Max.	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Single side cooled, T _c =60°C	150			1200	A
I _{F(RMS)}	RMS forward current					1884	A
I _{RRM}	Repetitive peak current	at V _{RRM}	150			50	mA
I _{FSM}	Surge forward current	V _R =60%V _{RRM} , t=10ms half sine,	150			24	kA
I ² t	I ² t for fusing coordination					2880	10 ³ A ² s
V _{FO}	Threshold voltage		150			0.88	V
r _F	Forward slope resistance					0.18	mΩ
V _{FM}	Peak forward voltage	I _{FM} =3000A	25			1.56	V
R _{th(j-c)}	Thermal resistance Junction to case	D.C. Single side cooled per chip				0.052	°C/W
R _{th(c-h)}	Thermal resistance case to heatsink	D.C. Single side cooled per chip				0.022	°C/W
V _{iso}	Isolation voltage	50Hz, R.M.S, t=1min, I _{iso} :1mA(MAX)		3000			V
F _m	Terminal connection torque(M12)			12.0		16.0	N·m
	Mounting torque(M8)			10.0		12.0	N·m
T _{vj}	Junction temperature			-40		150	°C
T _{stg}	Stored temperature			-40		125	°C
W _t	Weight				3230		g
Outline	M15						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7






Fig.8



MD1200D**W

MR1200D**W

MC1200D**W



Unmarked dimensional tolerance : ±0.5mm