

Features :

- Isolated mounting base 3000V~
- Pressure contact technology with Increased power cycling capability
- Space and weight saving

Typical Applications

- AC/DC Motor drives
- Various rectifiers
- DC supply for PWM inverter

V_{DSM}, V_{RSM}	V_{DRM}, V_{RRM}	品名
900V	800V	Mx350TH80C
1100V	1000V	Mx350TH100C
1300V	1200V	Mx350TH120C
1500V	1400V	Mx350TH140C
1700V	1600V	Mx350TH160C
1900V	1800V	Mx350TH180C

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	$T_j(^{\circ}\text{C})$	VALUE			UNIT
				Min	Type	Max	
$I_{T(AV)}$	Mean on-state current	180° half sine wave 50Hz Single side cooled, $T_c=85^{\circ}\text{C}$	125			350	A
$I_{T(RMS)}$	RMS on-state current					549	A
I_{DRM} I_{RRM}	Repetitive peak current	at V_{DRM} at V_{RRM}	125			35	mA
I_{TSM}	Surge on-state current	10ms half sine wave $V_R=60\%V_{RRM}$	125			11	kA
I^2t	I^2t for fusing coordination					605	$\text{A}^2\text{s} \times 10^3$
V_{TO}	Threshold voltage		125			0.95	V
r_T	On-state slope resistance					0.36	$\text{m}\Omega$
V_{TM}	Peak on-state voltage	$I_{TM}=1050\text{A}$	25			1.45	V
dv/dt	Critical rate of rise of off-state voltage	$V_{DM}=67\%V_{DRM}$	125			1000	$\text{V}/\mu\text{s}$
di/dt	Critical rate of rise of on-state current	Gate source 1.5A $t_r \leq 0.5\mu\text{s}$ Repetitive	125			200	$\text{A}/\mu\text{s}$
I_{GT}	Gate trigger current	$V_A=12\text{V}$, $I_A=1\text{A}$	25	30		180	mA
V_{GT}	Gate trigger voltage			0.8		2.5	V
I_H	Holding current			10		150	mA
V_{GD}	Non-trigger gate voltage	$V_{DM}=67\%V_{DRM}$	125	0.2			V
$R_{th(j-c)}$	Thermal resistance Junction to case	Single side cooled per chip				0.09	$^{\circ}\text{C}/\text{W}$
$R_{th(c-h)}$	Thermal resistance case to heatsink	Single side cooled per chip				0.04	$^{\circ}\text{C}/\text{W}$
V_{iso}	Isolation voltage	50Hz,R.M.S., $t=1\text{min}$, $I_{iso}:1\text{mA}(\text{MAX})$		3000			V
F_m	Terminal connection torque(M10)				12.0		N·m
	Mounting torque(M6)				6.0		N·m
T_{vj}	Junction temperature			-40		125	$^{\circ}\text{C}$
T_{stg}	Stored temperature			-40		125	$^{\circ}\text{C}$
W_t	Weight				1275		g
Outline	M06						




Fig1




Fig3




Fig5




Fig2




Fig4




Fig6




Fig7




Fig8




Fig9





Fig10



MD350TH**C

MR350TH**C

MC350TH**C

