


Features

- Low forward voltage drop
- High reverse voltage
- Hermetic metal cases with ceramic insulators

Typical Applications

- All purpose high power rectifier diodes
- High power resistance welding equipment
- Non-controllable and half-controllable rectifiers
- Controlled rectifiers

$I_{F(AV)}$ **1700 A**
 V_{RRM} **200~1000 V**
 I_{FSM} **18 KA**
 I^2t **1620 10³A²S**



SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T _J (°C)	VALUE			UNIT
					Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled,	T _C =85°C	190			1700	A
V _{RRM}	Repetitive peak reverse voltage	tp=10ms		190	200		1000	V
I _{RRM}	Repetitive peak current	at V _{RRM}		190			40	mA
I _{FSM}	Surge forward current	10ms half sine wave V _R =0.6V _{RRM}		190			18	kA
I ² t	I ² t for fusing coordination						1620	A ² s*10 ³
V _{FO}	Threshold voltage			190			0.81	V
r _F	Forward slope resistance						0.23	mΩ
V _{FM}	Peak forward voltage	I _{FM} =4400A, F=15kN		190			1.82	V
Q _{rr}	Recovery charge	I _{FM} =2000A, tp=2000μs, di/dt=-20A/μs, V _R =50V		190		1900		μC
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 15.0kN					0.035	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink						0.008	
F _m	Mounting force				10		20	kN
T _{stg}	Stored temperature				-40		190	°C
W _t	Weight					240		g
Outline	P39							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8

